


Features

- Enhancement mode
- VitoMOS® II Technology
- 100% Avalanche Tested, 100% Rg Tested

V_{DS}	60	V
$R_{DS(on),TYP@ V_{GS}=10V}$	6	mΩ
$R_{DS(on),TYP@ V_{GS}=4.5V}$	9.2	mΩ
I_D (Wire bond Limited)	31	A



Part ID	Package Type	Marking	Packing
VSE008N06MS-K	PDFN3333	08N06M	5000PCS/Reel



Maximum ratings, at $T_A = 25^\circ\text{C}$, unless otherwise specified

Symbol	Parameter		Rating	Unit
$V_{(BR)DSS}$	Drain-Source breakdown voltage		60	V
V_{GS}	Gate-Source voltage		± 20	V
I_S	Diode continuous forward current (Wire bond limited)	$T_C = 25^\circ\text{C}$	31	A
I_D	Continuous drain current @ $V_{GS}=10V$ (Wire bond limited)	$T_C = 25^\circ\text{C}$	31	A
I_D	Continuous drain current @ $V_{GS}=10V$ (Wire bond limited)	$T_C = 100^\circ\text{C}$	31	A
I_{DM}	Pulse drain current tested ①	$T_C = 25^\circ\text{C}$	209	A
I_{DSM}	Continuous drain current @ $V_{GS}=10V$	$T_A = 25^\circ\text{C}$	13	A
		$T_A = 70^\circ\text{C}$	11	A
E_{AS}	Avalanche energy, single pulsed ②		110	mJ
P_D	Maximum power dissipation ③	$T_C = 25^\circ\text{C}$	42	W
		$T_C = 100^\circ\text{C}$	17	W
P_{DSM}	Maximum power dissipation ④	$T_A = 25^\circ\text{C}$	2.3	W
		$T_A = 70^\circ\text{C}$	1.5	W
T_{STG}, T_J	Storage and Junction Temperature Range		-55 to 150	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Typical	Max	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case ⑤	2.5	3	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient ⑥	46	55	$^\circ\text{C/W}$

Electrical Characteristics

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
Static Electrical Characteristics @ T _j =25°C (unless otherwise stated)						
V(BR)DSS	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	60	--	--	V
IDSS	Zero Gate Voltage Drain Current(T _j =25°C)	V _{DS} =60V,V _{GS} =0V	--	--	1	μA
	Zero Gate Voltage Drain Current(T _j =125°C)⑦	V _{DS} =60V,V _{GS} =0V	--	--	100	μA
IGSS	Gate-Body Leakage Current	V _{GS} =±20V,V _{DS} =0V	--	--	±100	nA
VGS(th)	Gate Threshold Voltage	V _{DS} =V _{GS} ,I _D =250μA	1.2	1.7	2.3	V
RDS(on)	Drain-Source On-State Resistance ⑧	V _{GS} =10V, I _D =30A	--	6	8	mΩ
		(T _j =100°C)⑦	--	7.8	--	mΩ
RDS(on)	Drain-Source On-State Resistance ⑧	V _{GS} =4.5V, I _D =20A	--	9.2	12	mΩ
Dynamic Electrical Characteristics @ T _j = 25°C (unless otherwise stated)						
Ciss	Input Capacitance ⑦	V _{DS} =30V,V _{GS} =0V, f=1MHz	530	1065	1860	pF
Coss	Output Capacitance ⑦		170	340	590	pF
Crss	Reverse Transfer Capacitance ⑦		10	25	40	pF
Rg	Gate Resistance	f=1MHz	0.2	0.9	1.8	Ω
Qg(10V)	Total Gate Charge ⑦	V _{DS} =30V,I _D =30A, V _{GS} =10V	--	23	40	nC
Qg(4.5V)	Total Gate Charge ⑦		--	12	21	nC
Qgs	Gate-Source Charge ⑦		--	3.6	6.3	nC
Qgd	Gate-Drain Charge ⑦		--	6.3	11	nC
Switching Characteristics ⑦						
Td(on)	Turn-on Delay Time	V _{DD} =30V, I _D =30A, R _G =3Ω, V _{GS} =10V	--	6.4	--	ns
Tr	Turn-on Rise Time		--	46	--	ns
Td(off)	Turn-Off Delay Time		--	19	--	ns
Tf	Turn-Off Fall Time		--	22	--	ns
Source- Drain Diode Characteristics@ T _j = 25°C (unless otherwise stated)						
VSD	Forward on voltage	I _{SD} =30A,V _{GS} =0V	--	0.89	1	V
Trr	Reverse Recovery Time ⑦	V _{DD} =30V, I _{sd} =30A, V _{GS} =0V	--	22	44	ns
Qrr	Reverse Recovery Charge ⑦	di/dt=100A/μs	--	11	22	nC

NOTE:

- ① Single pulse; pulse width ≤ 100μs.
- ② This value is based on starting T_j = 25°C, L = 0.5mH, R_G = 25Ω, I_{AS} = 21A, V_{GS} = 10V; 100% FT tested at L = 0.5mH, I_{AS} = 12A.
- ③ The power dissipation Pd is based on T_j(max), using junction-to-case thermal resistance RθJC.
- ④ The power dissipation PdsM is based on T_j(max), using junction-to-ambient thermal resistance RθJA.
- ⑤ These tests are performed respectively with the device mounted on a 1 in2 pad and a minimum pad of 2oz. Copper FR-4 board in a still air environment with TA=25°C, using Transient Dual Interface method to acquire RθJC.
- ⑥ These tests are performed with the device mounted on 1 in2 FR-4 board with 2oz. Copper, in a still air environment with TA=25°C.
- ⑦ Guaranteed by design, not subject to production testing.
- ⑧ Pulse width ≤ 380μs; duty cycles 2%.

Typical Characteristics




Fig1. Typical Output Characteristics




Fig2. Typical $V_{GS(TH)}$ Gate-Source Voltage Vs. T_j




Fig3. Typical Transfer Characteristics




Fig4. Typical Normalized On-Resistance Vs. T_j




Fig5. Typical On Resistance Vs Gate-Source Voltage




Fig6. Typical On Resistance Vs Drain Current

Typical Characteristics




Fig7. Typical Source-Drain Diode Forward Voltage




Fig8. Maximum Safe Operating Area




Fig9. Typical Capacitance Vs. Drain-Source Voltage




Fig10. Typical Gate Charge Vs. Gate-Source Voltage




Fig11. Power Dissipation Vs. Case Temperature




Fig12. Maximum Drain Current Vs. Case Temperature

Typical Characteristics




Fig13 . Normalized Maximum Transient Thermal Impedance




Fig14. Unclamped Inductive Test Circuit and waveforms





Fig15. Switching Time Test Circuit and waveforms

Marking Information



1st line: Vergiga Code (Vs)

2nd line: Part Number (08N06M)

3rd line: Date code (XXXYWW)


XXX: Wafer Lot Number Code , code changed with Lot Number

Y: Year Code , refer to table below

WW: Week Code (01 to 53)

Code	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T
Year	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030

PDFN3333 Package Outline Data



Symbol	DIMENSIONS (unit : mm)		
	Min	Typ	Max
A	0.70	0.75	0.80
b	0.25	0.30	0.35
C	0.10	0.15	0.25
D	3.25	3.35	3.45
D1	3.00	3.10	3.20
D2	1.48	1.58	1.68
D3	--	0.13	--
E	3.00	3.20	3.40
E1	3.00	3.10	3.20
E2	2.39	2.49	2.59
e	0.65 BSC		
H	0.30	0.39	0.50
L	0.30	0.40	0.50
L1	--	0.13	--
θ	--	10°	12°
M	*	*	0.15

* Not specified

1 Notes:

1. Follow JEDEC MO-240 variation CA.
2. Dimensions "D1" and "E1" do NOT include mold flash protrusions or gate burrs.
3. Dimensions "D1" and "E1" include interterminal flash or protrusion. Interterminal flash or protrusion shall not exceed 0.25mm per side.

Customer Service

Sales and Service:

sales@vgsemi.com

Vergiga Semiconductor CO., LTD

TEL: (86-755) -26902410

FAX: (86-755) -26907027

WEB: www.vergiga.com